



226

14/2 UTP Cable
 Audio, Control, and Low Voltage Power

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	
• Number of Conductors	2
• AWG Size	14
• Conductor Stranding	19x27
• Conductor Type	Bare copper
• Nominal DCR	2.7 Ohm/1000ft
• Cabling Lay Length	4 in
• Twists/Foot	3 twist/ft
INSULATION PARAMETER	
• Insulation Type	Thermoplastic
• Insulation Thickness	0.012 in
• Insulation Color Code	1. Black 2.White
SHIELDING PARAMETER	
• Shield Type	None
ELECTRICAL CHARACTERISTICS	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.23 in
Plenum	No
NEC UL Rating	CL3R, FPLR
RoHS Compliant	Yes
Pull Tension	79 lbs
Bend Radius	2.07 in
Cable Weight	42 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



226

14/2 UTP Cable

Related Products

RELATED PRODUCTS	
Plenum Number	25226B
Aquaseal Direct Burial Number	AQ226
SpeakOn Panel Mount	CN-NL4MP