



230

22/3 Solid Unshielded CMR

Audio and Control

Construction & Dimensions

| | |
|--------------------------------------|-----------------------|
| CONSTRUCTION & DIMENSIONS | |
| CONDUCTOR PARAMETER | |
| • Number of Conductors | 3 |
| • AWG Size | 22 |
| • Conductor Stranding | Solid |
| • Conductor Type | Bare copper |
| • Nominal DCR | 17.5 Ohm/1000ft |
| INSULATION PARAMETER | |
| • Insulation Type | Th rmoplastic |
| • Insulation Thi kness | 0.007 in |
| • Insulation Color Code | 1.Black,2.Red,3.White |
| SHIELDING PARAMETER | |
| • Shield Type | None |
| ELECTRICAL CHARACTERISTICS | |

Overall Construction

| | |
|--|----------|
| OVERALL CONSTRUCTION PARAMETERS | |
| Jacket Type | PVC |
| Jacket Thi kness | 0.017 in |
| Nominal Cable O.D. | 0.125 in |
| Plenum | No |
| NEC UL Rating | CMR, CMG |
| RoHS Compliant | Yes |
| Pull Tension | 23 lbs |
| Bend Radius | 1.125 in |
| Cable Weight | 16 lbs |

Overall Electrical & Optical Characteristics

| | |
|---|-----------------------|
| OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS | |
| UL Flammability | UL1666 Vertical Shaft |
| CSA Flammability | FT4 |
| Operating Range | -20 to 60 Deg C |
| UL Voltage Rating | 300 |

Related Products

RELATED PRODUCTS