



246

14/4 UTP CMR
 Audio, Control, and Low Voltage Power

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	
• Number of Conductors	4
• AWG Size	14
• Conductor Stranding	19x27
• Conductor Type	Bare copper
• Nominal DCR	2.7 Ohm/1000ft
• Cabling Lay Length	4.75 in
INSULATION PARAMETER	
• Insulation Type	Th rmoplastic
• Insulation Thi kness	0.012 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	
• Shield Type	None
ELECTRICAL CHARACTERISTICS	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	PVC
Jacket Thi kness	0.017 in
Nominal Cable O.D.	0.278 in
Plenum	No
NEC UL Rating	CL3R, FPLR
RoHS Compliant	Yes
Pull Tension	190 lbs
Bend Radius	2.502 in
Cable Weight	79 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



246

14/4 UTP CMR

Audio, Control, and Low Voltage Power

Related Products

RELATED PRODUCTS	
Plenum Number	25246B
Aquaseal Direct Burial Number	AQ246
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP