

Detailed Specifications & Technical Data



25226B

2 Conductor 14 AWG Unshielded CL3P Rated
Audio, Control and Low Voltage Power

CONDUCTOR PARAMETERS	
Number of Conductors	2
AWG Size	14
Conductor Stranding	19 x 27
Conductor Type	Bare Copper
Nominal DCR	2.7 Ω /1000 ft
Cabling Lay Length	3.75 in
Twists / Foot	3.2 twist/ft
INSULATION PARAMETERS	
Insulation Type	Plenum PVC
Insulation Thickness	0.012 in
Insulation Color Code	1. Black 2. Red
SHIELDING PARAMETERS	
Shield Type	None

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.223 in
Plenum	Yes
NEC UL Rating	CL3P, FPLP
RoHS Compliant	Yes
Pull Tension	84 lbs
Bend Radius	2.007 in
Cable Weight	36 lbs

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60°C
UL Voltage Rating	300

RELATED PRODUCTS	
Non Plenum Number	226
Aquaseal Direct Burial Number	AQ226
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP