



256350

RG6/U HD-SDI Plenum
 HD-SDI Digital Video

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	1
• AWG Size	18
• Conductor Stranding	Solid
• Conductor Type	Bare Copper
• Nominal DCR	6.5 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Foam FEP
• Insulation Thi kness	0.17 in
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Shield Type 2	95% Tinned Copper Braid
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	75 Ohm
• Nom. Cap. Between Conductors	16.2 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Nominal Cable O.D.	0.236 in
Plenum	Yes
NEC UL Rating	CMP
RoHS Compliant	Yes
Pull Tension	75 lbs
Bend Radius	2.36 in
Cable Weight	36 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	82 %
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300



256350

RG6/U HD-SDI Plenum
HD-SDI Digital Video

Attenuation

FREQUENCY (MHz)	ATTENUATION (db/100ft)
1 MHz	0.23 dB
3.6 MHz	0.45 dB
10 MHz	0.75 dB
71.5 MHz	1.77 dB
135 MHz	2.45 dB
270 MHz	3.3 dB
360 MHz	4 dB
540 MHz	5.1 dB
720 MHz	5.9 dB
1000 MHz	7.3 dB
2250 MHz	11.59 dB
3000 MHz	13.71 dB

Related Products

RELATED PRODUCTS	
Non Plenum Number	6350
BNC Crimp	CN-BM73-4
BNC Compression	CN-BNC6MCV
RCA Compression	CN-CSRCA-6