



**280**

18/5 Unshielded CMR  
 Audio and Control

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	5
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Bare copper
• Nominal DCR	6.2 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Th rmoplastic
• Insulation Thi kness	0.008 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green,5. Brown
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thi kness	0.017 in
Nominal Cable O.D.	0.205 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	112 lbs
Bend Radius	1.845 in
Cable Weight	41 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### 280

18/5 Unshielded CMR  
Audio and Control

## Related Products

RELATED PRODUCTS	-
Plenum Number	25186B