



281

18/7 Unshielded CMR
 Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	7
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Bare copper
• Nominal DCR	6.2 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Th rmoplastic
• Insulation Thi kness	0.008 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green,5. Brown,6.Blue,7.Orange
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thi kness	0.017 in
Nominal Cable O.D.	0.225 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	132 lbs
Bend Radius	2.025 in
Cable Weight	54 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



281

18/7 Unshielded CMR
Audio and Control

Related Products

RELATED PRODUCTS	-
Plenum Number	25188B
Aquaseal Number	AQC188