



## 2815B

RG59/U CCTV + Power  
Analog Video, CCTV Video

### Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-	
Component	Video	Power
CONDUCTOR PARAMETER	-	
• Number of Conductors	1	2
• AWG Size	20	18
• Conductor Stranding	Solid	7x26
• Conductor Type	Bare Copper	Bare Copper
• Nominal DCR	10.1 Ohm/1000ft	6.2 Ohm/1000ft
INSULATION PARAMETER	-	
• Insulation Type	Foam Polyethylene	PVC
• Insulation Thickness	0.138 in	0.008 in
• Insulation Color Code		1. Black 2.Red
SHIELDING PARAMETER	-	
• Shield Type	95% Bare Copper Braid	
ELECTRICAL CHARACTERISTICS	-	
• Nominal Impedance	75 Ohm	
• Nom. Cap. Between Conductors	16.2 pF/ft	

### Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	3
Jacket Type	PVC - Siamese
Nominal Cable O.D.	.232x.465 in
Plenum	No
NEC UL Rating	CMR
RoHS Compliant	Yes
Bend Radius	4.65 in
Cable Weight	48 lbs

### Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	80 %
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



### **2815B**

RG59/U CCTV + Power

Analog Video, CCTV Video

## Attenuation

FREQUENCY (MHz)	ATTENUATION (db/100ft)
1 MHz	0.29 dB
10 MHz	0.68 dB
50 MHz	1.8 dB
100 MHz	3 dB
200 MHz	3.54 dB
400 MHz	4.71 dB
700 MHz	6.4 dB
900 MHz	7.33 dB
1000 MHz	7.8 dB

## Related Products

RELATED PRODUCTS	-
Plenum Number	252815
BNC Crimp	CN-BM74-32
BNC Compression	CN-BNC59MCV