



## 352

3Cond. Shld/Unshld 22AWG CMR  
Audio, Control and Intercom

### Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-	
Component	Shielded	Unshielded
CONDUCTOR PARAMETER	-	
• Number of Conductors	2	1
• AWG Size	22	22
• Conductor Stranding	7x30	7x30
• Conductor Type	Bare Copper	Bare Copper
• Nominal DCR	17 Ohm/1000ft	17 Ohm/1000ft
INSULATION PARAMETER	-	
• Insulation Type	Th rmoplastic	Th rmoplastic
• Insulation Thi kness	0.007 in	0.007 in
• Insulation Color Code	1. Black 2.Red	White
SHIELDING PARAMETER	-	
• Shield Type	Overall 100% Aluminum Foil	None
• Drain Wire Type	Tinned Copper	
• Drain Wire AWG	24 AWG	
ELECTRICAL CHARACTERISTICS	-	
• Nom. Cap. Between Conductors	34 pF/ft	
• Nom. Cap. Conductor to Shield	67 pF/ft	

### Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	3
Jacket Type	PVC
Jacket Thi kness	0.017 in
Nominal Cable O.D.	0.162 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	32 lbs
Bend Radius	1.458 in
Cable Weight	18 lbs

### Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### 352

3Cond. Shld/Unshld 22AWG CMR  
Audio, Control and Intercom

## Related Products

RELATED PRODUCTS	-
Plenum Number	25352B
Aquaseal Number	AQC352