

Product: **60993BS**

2 Conductor 14 AWG Stranded Unshielded FPLP

Fire Alarm Initiating Devices and NAC



CONDUCTOR PARAMETERS	
Number of Conductors	2
AWG Size	14
Conductor Stranding	Standard
Conductor Type	Bare Copper
Nominal DCR	2.6 Ω/1000 ft
Cable Lay Length	1.75 in
INSULATION PARAMETERS	
Insulation Type	Plenum PVC
Insulation Thickness	.009 in
Insulation Color Code	1. Black 2. Red
Cabling Lay Length	3.25 in
Twists/Foot	3.7
SHIELDING PARAMETERS	
Shield Type	Unshielded
ELECTRICAL CHARACTERISTICS	
Nom. Cap. Between Conductors	34 pf/ft

OVERALL CONSTRUCTION PARAMETERS	
Total Number of Conductors	2
Jacket Type	Plenum PVC
Nom. Jacket Thickness	.015 in
Nom. Cable O.D.	.214 in
Plenum	Yes - Indoor
NEC UL Rating	FPLP
RoHS Compliant	Yes
Bend Radius	1.83
Pull Tension	99 lbs
Cable Weight	41 lbs

OVERALL ELECTRICAL CHARACTERISTICS	
UL Flammability	NFPA 262 Plenum
Operating Range	0° to 75°C
UL Voltage Rating	300V