

700

14/4 Solid Unshielded FPLR
 Fire Alarm Signaling

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	14
• Conductor Stranding	Solid
• Conductor Type	Bare Copper
• Nominal DCR	2.6 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Th rmoplastic
• Insulation Thi kness	0.01 in
• Insulation Color Code	1.Black,2.Red,3.Brown,4.Blue
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	22 pF/ft


Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thi kness	0.022 in
Nominal Cable O.D.	0.25 in
Plenum	No
NEC UL Rating	FPLR
RoHS Compliant	Yes
Pull Tension	175 lbs
Bend Radius	2.25 in
Cable Weight	67 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



700

14/4 Solid Unshielded FPLR
Fire Alarm Signaling

Related Products

RELATED PRODUCTS	-
Plenum Number	60700B
Aquaseal Direct Burial Number	AQ246