



751

2 Pair 18AWG Unshielded CMR Rated
 Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	2
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Bare copper
• Nominal DCR	6.2 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.008 in
• Insulation Color Code	1. Black-Rd, Red, 2.Black-Wh, White
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	23 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	4
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.257 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Bend Radius	2.313 in
Cable Weight	38 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



751

2 Pair 18AWG Unshielded CMR Rated
Audio and Control

Related Products

RELATED PRODUCTS	-
Plenum Number	25751B