



**841**

RG6/U BC Type CATV Dual Shield  
 CATV/MATV DBS

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	1
• AWG Size	18
• Conductor Stranding	Solid
• Conductor Type	Bare copper
• Nominal DCR	6.5 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Foam Polyethylene
• Insulation Thi kness	0.18 in
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Shield Type 2	Aluminum Braid
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	75 Ohm
• Nom. Cap. Between Conductors	16.2 pF/ft

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thi kness	0.026 in
Nominal Cable O.D.	0.265 in
Plenum	No
NEC UL Rating	CATV, CM
RoHS Compliant	Yes
Pull Tension	70 lbs
Bend Radius	2.65 in
Cable Weight	32 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	82 %
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



**841**

RG6/U BC Type CATV Dual Shield  
CATV/MATV DBS

**Attenuation**

FREQUENCY (MHz)	ATTENUATION (db/100ft)
5 MHz	0.57 dB
55 MHz	1.45 dB
100 MHz	1.85 dB
270 MHz	3.07 dB
400 MHz	3.85 dB
540 MHz	4.6 dB
750 MHz	5.4 dB
1000 MHz	6.3 dB
1450 MHz	8.05 dB
2250 MHz	9.99 dB
3000 MHz	11.9 dB

**Related Products**

RELATED PRODUCTS	-
Plenum Number	25841
Aquaseal Number	AQC841
“F” Type Crimp	CN-F56ALM
“F” Type Compression	CN-F6MCV