



980

18/2 Solid Unshielded FPLR
 Fire Alarm Signaling

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	18
• Conductor Stranding	Solid
• Conductor Type	Bare Copper
• Nominal DCR	6.5 Ohm/1000ft
• Cabling Lay Length	3 in
• Twists/Foot	4 twist/ft
INSULATION PARAMETER	-
• Insulation Type	Thermoplastic
• Insulation Thickness	0.008 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	20 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.022 in
Nominal Cable O.D.	0.146 in
Plenum	No
NEC UL Rating	FPLR
RoHS Compliant	Yes
Pull Tension	39 lbs
Bend Radius	1.313 in
Cable Weight	18 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 75 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



980

18/2 Solid Unshielded FPLR
Fire Alarm Signaling

Related Products

RELATED PRODUCTS	-
Plenum Number	60980B
Aquaseal Number	AQC224
Aquaseal Direct Burial Number	AQ224