



## AQC369

6 Conductors (2 Shielded, 4 Unshielded) 22AWG Solid CMP Rated  
 Audio, Control, Alarm Indoor/Outdoor



## Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-	
Component	Shielded	Unshielded
<b>CONDUCTOR PARAMETER</b>	-	
• Number of Conductors	2	4
• AWG Size	22	22
• Conductor Stranding	Solid	Solid
• Conductor Type	Bare Copper	Bare Copper
• Nominal DCR	17 Ohm/1000ft	17 Ohm/1000ft
<b>INSULATION PARAMETER</b>	-	
• Insulation Type	PVC	PVC
• Insulation Thickness	0.01 in	0.01 in
• Insulation Color Code	1. Black 2.Red	1. White 2.Green 3.Brown 4.Blue
<b>SHIELDING PARAMETER</b>	-	
• Shield Type	Overall 100% Aluminum Foil	None
• Shield Type 2	Aquaseal Water Blocking Tape	
• Drain Wire Type	Tinned Copper	
• Drain Wire AWG	22 AWG	
<b>ELECTRICAL CHARACTERISTICS</b>	-	
• Nom. Cap. Between Conductors	54 pF/ft	
• Nom. Cap. Conductor to Shield	97 pF/ft	

## Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	6
Jacket Type	UV Resistant PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.24 in
Plenum	No
NEC UL Rating	CM, CL3
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	69 lbs
Bend Radius	2.16 in
Cable Weight	29 lbs

## Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### **AQC369**

6 Conductors (2 Shielded, 4 Unshielded) 22AWG Solid CMP Rated  
Audio, Control, Alarm Indoor/Outdoor



## Related Products

RELATED PRODUCTS