



AQC430

2 pair 22 AWG Industrial Shielded CM AQUASEAL
Audio and Control Indoor/Outdoor



Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	2
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Bare copper
• Nominal DCR	17 Ohm/1000 ft
INSULATION PARAMETER	-
• Insulation Type	PVC
• Insulation Thickness	0.01 in
• Insulation Color Code	1. Black/Red-Red, 2. Black/White-White
SHIELDING PARAMETER	-
• Shield Type	Individually Shielded
• Shield Type 2	Aquaseal Water Blocking Tape
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	55 pF/ft
• Nom. Cap. Conductor to Shield	99 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS

Total Number of Conductors	4
Jacket Type	UV Resistant PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.250 in
Plenum	No
NEC UL Rating	CM, CL3
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	60 lbs
Bend Radius	3.42 in
Cable Weight	29 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 90 Deg C
UL Voltage Rating	300



AQC430

2 pair 22 AWG Industrial Shielded CM AQUASEAL
Low Capacitance Audio and Control Indoor/Outdoor

Related Products

RELATED PRODUCTS	-
Plenum Number	D25430
Non Plenum Number	D430
3 Pin XLR Male	CN-NC3MX
3 Pin XLR Female	CN-NC3FX
3.5mm Stereo Mini	CN-NYS231