



D25291

22/2 Shielded Low Cap CMP
Audio and Control

Construction & Dimensions

| | |
|---------------------------------|----------------------------|
| CONSTRUCTION & DIMENSIONS | - |
| CONDUCTOR PARAMETER | - |
| • Number of Pairs | 1 |
| • AWG Size | 22 |
| • Conductor Stranding | 7x30 |
| • Conductor Type | Tinned Copper |
| • Nominal DCR | 17 Ohm/1000ft |
| INSULATION PARAMETER | - |
| • Insulation Type | FEP |
| • Insulation Thickness | 0.007 in |
| • Insulation Color Code | 1. Black 2.Red |
| SHIELDING PARAMETER | - |
| • Shield Type | Overall 100% Aluminum Foil |
| • Drain Wire Type | Tinned Copper |
| • Drain Wire AWG | 24 AWG |
| ELECTRICAL CHARACTERISTICS | - |
| • Nom. Cap. Between Conductors | 35 pF/ft |
| • Nom. Cap. Conductor to Shield | 67 pF/ft |

Overall Construction

| | |
|---------------------------------|-----------------|
| OVERALL CONSTRUCTION PARAMETERS | - |
| Jacket Type | Flexible Plenum |
| Jacket Thickness | 0.017 in |
| Nominal Cable O.D. | 0.134 in |
| Plenum | Yes |
| NEC UL Rating | CMP |
| RoHS Compliant | Yes |
| Pull Tension | 33 lbs |
| Bend Radius | 1.206 in |
| Cable Weight | 14 lbs |

Overall Electrical & Optical Characteristics

| | |
|--|-----------------|
| OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS | - |
| UL Flammability | NFPA 262 Plenum |
| Operating Range | -0 to 60 Deg C |
| UL Voltage Rating | 300 |



D25291

22/2 Shielded Low Cap CMP
Audio and Control

Related Products

| RELATED PRODUCTS | - |
|-------------------|-----------|
| Non Plenum Number | 77291 |
| 3 Pin XLR Male | CN-NC3MX |
| 3 Pin XLR Female | CN-NC3FX |
| 3.5mm Stereo Mini | CN-NYS231 |