



## D253652

3 Pair 22AWG Foil Shield CMP Rated  
Serial Data and Control Low Capacitance

### Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	3
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Tinned Copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	FEP
• Insulation Thi kness	0.007 in
• Insulation Color Code	1.Black-Red,2.Black-White,3.Black-Green
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	55 Ohm
• Nom. Cap. Between Conductors	26 pF/ft
• Nom. Cap. Conductor to Shield	47 pF/ft

### Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	6
Jacket Type	Flexible Plenum
Jacket Thi kness	0.015 in
Nominal Cable O.D.	0.204 in
Plenum	Yes
NEC UL Rating	CMP
RoHS Compliant	Yes
Bend Radius	1.835 in

### Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	72 %
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### **D253652**

3 Pair 22AWG Foil Shield CMP Rated  
Serial Data and Control Low Capacitance

## Related Products

RELATED PRODUCTS	-
Non Plenum Number	D3652