



D439

4Pr. 22AWG Ind. Shielded CM
Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	4
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Tinned Copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thi kness	0.006 in
• Insulation Color Code	1.Black-Red, 2. Black-White 3. Black-Green 4. Black-Blue
SHIELDING PARAMETER	-
• Shield Type	Individually Shielded
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	34 pF/ft
• Nom. Cap. Conductor to Shield	67 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thi kness	0.017 in
Nominal Cable O.D.	0.28 in
Plenum	No
NEC UL Rating	CM
RoHS Compliant	Yes
Pull Tension	80 lbs
Bend Radius	2.52 in
Cable Weight	47 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



D439

4Pr. 22AWG Ind. Shielded CM
Audio and Control

Related Products

RELATED PRODUCTS	-
Plenum Number	D25439
Aquaseal Number	AQC439
3 Pin XLR Male	CN-NC3MX
3 Pin XLR Female	CN-NC3FX
3.5mm Stereo Mini	CN-NYS231