



**D441**

3Pr. 18AWG Ind. Shielded CM  
 Audio and Control

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	3
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Tinned Copper
• Nominal DCR	10.5 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thi kness	0.008 in
• Insulation Color Code	1. Black-Rd, Red, 2.Black-Wh, White 3.Black-Gn, Green
SHIELDING PARAMETER	-
• Shield Type	Individually Shielded
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	40 pF/ft
• Nom. Cap. Conductor to Shield	73 pF/ft

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	6
Jacket Type	PVC
Jacket Thi kness	0.017 in
Nominal Cable O.D.	0.285 in
Plenum	No
NEC UL Rating	CM
RoHS Compliant	Yes
Pull Tension	67 lbs
Bend Radius	2.565 in
Cable Weight	55 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### **D441**

3Pr. 18AWG Ind. Shielded CM  
Audio and Control

## Related Products

RELATED PRODUCTS