



WP9C014

4 Fiber OM3 Breakout OFNP
 Audio, Video and Data - Digital Video

Construction & Dimenstions

CONDUCTOR PARAMETERS	
Conductor Type	Optical Fiber
Number Of Fibers	4
Fiber Optic Size	50
OM Fiber Optic Rating	OM3
INSULATION PARAMETERS	
Insulation Type	Th rmoplastic
Buffer Size	900 m
Insulation Color Code	1.Blue,2.Orange,3.Green,4.Brown
SHIELDING PARAMETERS	
Fiber Optic Design	Breakout
ELECTRICAL CHARACTERISTICS	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	Plenum PVC
Nominal Cable O.D.	0.3 in
Plenum	No
NEC UL Rating	OFNP
RoHS Compliant	Yes
TIA Test	ANSI/TIA-568-C.3
Pull Tension	300 lbs
Bend Radius	3 in
Cable Weight	21 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT6
Operating Range	-40 to 70 Deg C
Operating Wavelength	850/1300
Min. OFL Bandwidth	1500/500
Max. Attenuation	3.50/1.25