



25301B

22/3 Shielded CMP
 Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	3
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Bare copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Plenum PVC
• Insulation Thi kness	0.007 in
• Insulation Color Code	1.Black,2.Red,3.White
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	54 pF/ft
• Nom. Cap. Conductor to Shield	97 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Jacket Thi kness	0.015 in
Nominal Cable O.D.	0.13 in
Plenum	Yes
NEC UL Rating	CMP
RoHS Compliant	Yes
Pull Tension	30 lbs
Bend Radius	1.17 in
Cable Weight	18 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



25301B

22/3 Shielded CMP

Audio and Control

Related Products

RELATED PRODUCTS	-
Non Plenum Number	301