

**360**

4 Cond Shld/Unshld 18AWG CMR
 Audio, Control and Intercom

Construction & Dimensions

CONSTRUCTION & DIMENSIONS		-
Component	Shielded	Unshielded
CONDUCTOR PARAMETER		-
• Number of Conductors	2	2
• AWG Size	18	18
• Conductor Stranding	7x26	7x26
• Conductor Type	Bare Copper	Bare Copper
• Nominal DCR	6.2 Ohm/1000ft	6.2 Ohm/1000ft
INSULATION PARAMETER		-
• Insulation Type	Th rmoplastic	Th rmoplastic
• Insulation Thi kness	0.007 in	0.007 in
• Insulation Color Code	1. Black 2.Red	1. White 2.Green
SHIELDING PARAMETER		-
• Shield Type	Overall 100% Aluminum Foil	None
• Drain Wire Type	Tinned Copper	
• Drain Wire AWG	22 AWG	
ELECTRICAL CHARACTERISTICS		-
• Nom. Cap. Between Conductors	53 pF/ft	
• Nom. Cap. Conductor to Shield	103 pF/ft	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS		-
Total Number of Conductors		4
Jacket Type		PVC
Jacket Thi kness		0.017 in
Nominal Cable O.D.		0.205 in
Plenum		No
NEC UL Rating		CMR, CMG
RoHS Compliant		Yes
Pull Tension		103 lbs
Bend Radius		1.845 in
Cable Weight		39 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS		-
UL Flammability		UL1666 Vertical Shaft
CSA Flammability		FT4
Operating Range		-20 to 60 Deg C
UL Voltage Rating		300

Detailed Specification & Technical Data



360

4 Cond Shld/Unshld 18AWG CMR
Audio, Control and Intercom

Related Products

RELATED PRODUCTS