



3753

4 Pair 18AWG Shielded CMR Rated
Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	4
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Bare copper
• Nominal DCR	10.2 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.008 in
• Insulation Color Code	1. Black-Rd, Red, 2.Black-Wh, White 3.Black-Gn, Green 4. Black-Bu, Blue
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	40 pF/ft
• Nom. Cap. Conductor to Shield	79 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	8
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.315 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Bend Radius	2.835 in
Cable Weight	72 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



3753

4 Pair 18AWG Shielded CMR Rated
Audio and Control



Related Products

RELATED PRODUCTS