

## Detailed Specifications & Technical Data

### Product: 60993B

2 Conductor 14AWG Solid Unshielded FPLP  
 Fire Alarm Initiating Devices and NAC



Conductor Parameter	
No. of Conductors	2
AWG Size	14 AWG
Conductor Stranding	Solid
Conductor Type	Bare Copper
Nom. DCR	2.6 Ohm/1000ft
Insulation Parameter	
Insulation Type	Plenum PVC
Insulation Thickness	.010 in
Insulation Color Code	1.Black,2.Red
• Cabling Lay Length	3.25 in
• Twists/Foot	3.7 Twists/ft
Shielding Parameter	
Shield Type	Unshielded
Electrical Parameter	
• Nom. Cap. Between Conductors	34 pF/ft

Overall Construction Parameters	
Total No. of Conductors	2
Jacket Type	Plenum PVC
Nom. Jacket Thickness	.015"
Nom. Cable O.D.	.201
Plenum	Yes - Indoor Plenum
NEC UL Rating	FPLP
RoHS Compliant	Yes
Bend Radius	1.83 in
Pull Tension	99 lbs
Cable Weight	38

Overall Electrical Characteristics	
UL Flammability	NFPA 262 Plenum
OPERATING RANGE	-0 to 75 Deg C
UL VOLTAGE	300V