



## 653

4 Pair 22AWG Unshielded CMR Rated  
Audio and Control

### Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	4
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Bare copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Thermoplastic
• Insulation Thickness	0.007 in
• Insulation Color Code	1. Black-Rd, Red, 2.Black-Wh, White 3.Black-Gn, Green 4. Black-Bu, Blue
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	19 pF/ft

### Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	8
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.225 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Bend Radius	2.025 in
Cable Weight	34 lbs

### Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### **653**

4 Pair 22AWG Unshielded CMR Rated  
Audio and Control

## Related Products

RELATED PRODUCTS