



## 77292

20/2 Shielded Low Cap. CM  
Audio and Control

### Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	1
• AWG Size	20
• Conductor Stranding	7x28
• Conductor Type	Tinned Copper
• Nominal DCR	10.5 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polyethylene - PE
• Insulation Thi kness	0.016 in
• Insulation Color Code	1.Black,2.Clear
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	20 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	27 pF/ft
• Nom. Cap. Conductor to Shield	49 pF/ft

### Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thi kness	0.025 in
Nominal Cable O.D.	0.204 in
Plenum	No
NEC UL Rating	CM
RoHS Compliant	Yes
Pull Tension	39 lbs
Bend Radius	1.835 in
Cable Weight	22 lbs

### Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### 77292

20/2 Shielded Low Cap. CM  
Audio and Control

## Related Products

RELATED PRODUCTS	-
Plenum Number	D25292
3 Pin XLR Male	CN-NC3MX
3 Pin XLR Female	CN-NC3FX
3.5mm Stereo Mini	CN-NYS231