



77510

2 Pr. 22AWG Ind. Shielded CMR
Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Pairs	2
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Tinned Copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thi kness	0.008 in
• Insulation Color Code	1. Black-Red 2. White-Green
SHIELDING PARAMETER	-
• Shield Type	Individually Shielded - With Overall 100% Shield
• Drain Wire Type	Tinned Copper - (1Common Drain to all three sheilds)
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	50 Ohm
• Nom. Cap. Between Conductors	34 pF/ft
• Nom. Cap. Conductor to Shield	67 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Total Number of Conductors	4
Jacket Type	PVC
Jacket Thi kness	0.020 in
Nominal Cable O.D.	0.189 in
Plenum	No
NEC UL Rating	CMR
RoHS Compliant	Yes
Pull Tension	51 lbs
Bend Radius	1.9 in
Cable Weight	29 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



77510

2 Pr. 22AWG Ind. Shielded CMR
Audio and Control

Related Products

RELATED PRODUCTS	
3 Pin XLR Male	CN-NC3MX
3 Pin XLR Female	CN-NC3FX
3.5mm Stereo Mini	CN-NYS231