



C208

8/2 Unshielded TC
Large Venue Speaker Distribution

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	8
• Conductor Stranding	65x26
• Conductor Type	Bare copper
• Nominal DCR	0.7 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC-Nylon
• Insulation Thickness	0.038 in
• Insulation Color Code	1. Black 2.White
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.062 in
Nominal Cable O.D.	0.498 in
Plenum	No
NEC UL Rating	TC
RoHS Compliant	Yes
Pull Tension	410 lbs
Bend Radius	4.482 in

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	600



C208

8/2 Unshielded TC
Large Venue Speaker Distribution

Related Products

RELATED PRODUCTS	-