



**HA225**

2 Conductor 16AWG Unshielded CM Rated  
 Audio and Control

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	16
• Conductor Stranding	65x34
• Conductor Type	Bare Copper
• Nominal DCR	4.02 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.01 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.199 in
Plenum	No
NEC UL Rating	CM
RoHS Compliant	Yes
Bend Radius	1.791 in
Cable Weight	26 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### **HA225**

2 Conductor 16AWG Unshielded CM Rated  
Audio and Control

## Related Products

RELATED PRODUCTS	-
Plenum Number	25225B
Non Plenum Number	225
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP