

**HA245**

4 Conductor 16AWG Unshielded CM Rated
Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	16
• Conductor Stranding	26x30
• Conductor Type	Bare Copper
• Nominal DCR	4.02 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.01 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.242 in
Plenum	No
NEC UL Rating	CM
RoHS Compliant	Yes
Bend Radius	2.178 in
Cable Weight	48 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



HA245

4 Conductor 16AWG Unshielded CM Rated
Audio and Control

Related Products

RELATED PRODUCTS	-
Plenum Number	25245B
Non Plenum Number	245
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP