

**HA246**

4 Conductor 14AWG Unshielded CM Rated
Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	14
• Conductor Stranding	41x30
• Conductor Type	Bare Copper
• Nominal DCR	2.58 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polypropylene - PP
• Insulation Thickness	0.012 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.025 in
Nominal Cable O.D.	0.307 in
Plenum	No
NEC UL Rating	CL3
RoHS Compliant	Yes
Bend Radius	2.763 in
Cable Weight	76 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



HA246

4 Conductor 14AWG Unshielded CM Rated
Audio and Control

Related Products

RELATED PRODUCTS	-
Plenum Number	25246B
Non Plenum Number	246
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP